



**A family of low cost,
high performance
LCD indicators and
accessories**



Now available in standard and DIN sizes, the MITE Series 7999 time indicators offer unmatched ease-of-use, simplicity, performance and value. Two models (of either size) provide four timing ranges to cover applications such as coating/rinsing, baking and engine usage.

- Timers include models for second or minutes and seconds; or hours and minutes or hours and hundredths
- Compact, solid state design
- Front panel and remote reset
- NEMA-4/IP65 environmental sealing
- Easy-to-read, high contrast Liquid Crystal Display (LCD)
- UL recognized, CSA Certified
- Supplied with prewired plug-in connector
- Fast, easy mounting - minimal 1.2" (30mm) depth behind panel
- Very low priced - without sacrifice of performance or reliability

SPECIFICATIONS

Accuracy:
Timer: ± 20 ppm @ 20°C

Inputs: Contact closure or open collector

Display:
Standard Size Models: 7 digit, 0.315" (8mm) LCD
DIN Size Models: 7 digit, 7mm LCD

Reset:
Front panel (selectable), remote by contact closure or NPN transistor.

- Power Requirements:**
None; internal lithium battery with 10-year typical life
- Operating Temperature:** +14° to +144 °F (-10° to +60°C)
- Storage Temperature:** +4° to +144 °F (-20° to +60°C)

Model No.	Description
799988-510	LCD Time Indicator, Sec or Min-Sec, Standard Size
799988-610	LCD Time Indicator, Hr-Min or Hrs- ¹ / ₁₀₀ ths, Standard Size
79998D-510	LCD Time Indicator, Sec or Min-Sec, Din Size
79998D-610	LCD Time Indicator, Hr-Min or Hrs- ¹ / ₁₀₀ ths, Din Size

ACCESSORIES

AC/DC Input Module: Allows use of high voltage input signal of 5 to 240 VAC/DC. Connections are via screw terminations. For use with model 799988-510 or 799988-610: Part Number 329588-001; For use with model 79998D-510 or 79998D-610: Part Number 108940-0001

Screw Terminal Adaptor: Provides the convenience of screw terminal connection of input signal and remote reset. For use with 799988 models: Part Number 329590-001; For use with 79998D models: Part Number 108937-0001

